

**FULL HD OVER COAX USE YOUR EXISTING COAX CABLE****HDSDI** 2nd Generation**16 Channels****PRO-K5616****TRUE HYBRID DVR SYSTEM**


LIMITLESS GENUINE HYBRID DVR FOR
HD-SDI & ANALOG

FEATURES

- H.264 High Profile Compression
- Mobile Viewer for Various OS (iPad, iPhone, Android)
- Advanced PTZ Control
- Programmable Spot Out
- Superior Analog Video Quality with 3D-Comb Filter
- Relay Alarm Out Port (Dry Contact Type) with Master Alarm

FREE
DDNS SERVICE

HDMI
OUTPUT



*Rear Panel

XVST PRO-K5616

Compression	H.264 (High Profile)
Operating System	Embedded Linux
OS Firmware	Linux OS in Flash Memory
Signal Format	HD-SDI (720p, 1080i up to 1080p 30) / NTSC or PAL (Auto / Manual)
Memory	2GB DDR3 Memory
Video Input	16 (BNC)
Video Output	Composite: 1
VGA	1 Port (Max. 1920 x 1080)
HDMI	1 Port (Max. 1920 x 1080)
Multi Spot Out	1
Recording Rate (Max.)	480fps @1080i 30 / 480(400)fps@960H
Audio Input / Output	16 Input / 1 Output
Alarm Input	16 Input
Master Alarm	1
Alarm Output	16 (TTL) / 2 (Relay)
USB 2.0	4 x USB (2 x Front Panel, 2 x Rear Panel)
Ethernet	10 / 100 / 1000 Mbps Ethernet (RJ-45)
User Interface (GUI / Control Device)	Keypad, Mouse, PTZ Control, Remote Controller
Archive File Format	EXE (Video Clip) / AVI (Video Clip) / JPEG (Still Image)
NTP Server	Yes
GMT Time Zone	Yes
Auto DST	Yes
Recording Qualities	Super / High / Standard / Low
Recording Modes	Continuous / Alarm / Motion / Emergency
Motion Detection	Yes (30 x 20)
Playback Control	x1, x2, x4, x8, x16, x32, x64, Extreme
PTZ Control	RS-485 / 422 Serial Port (Terminal Block), RS-485 Through BNC (UTC)
Text Insertion (POS)	4
Multi Language	Arabic / Chinese (Simplified) / Chinese (Traditional) / Croatian / Czech / Danish / English / Finnish / French / German / Hungarian / Italian / Japanese / Korean / Persian / Polish / Portuguese / Russian / Spanish / Thai / Turkish
Central Monitoring Station	CMS Pro (Windows) / iCMS (MAC) / Web Client Pro
Mobile Viewer	iPad / iPhone / Android
Primary Storage	4 x SATA HDD, 1 x ODD
eSATA	1 Port
Clip Copy Storage	Built-in Internal DVR-RW, USB Memory Stick
Dimension (WxHxD)	430 mm x 88 mm x 380 mm / 16.93 inch x 3.46 inch x 14.96 inch (Rack Type)
Operating Temperature	5 °C~40 °C / 41 °F~104 °F
Operating Humidity	0% ~ 90%
Power Adapter	12V, 6A (72W)
Power	Max. 59.4W in Normal